

Permit No.:	
Date Received:	
By:	

## FIRE SPRINKLER AFFIDAVIT FOR ALTERATIONS OR TENANT IMPROVEMENTS

(1 to 10 SPRINKLER HEADS WITHOUT PLANS)

D :				
			Type of Construction:	
Suite:			DI.	
Contractor:			Phone:	
Number of Proposed o	r Altered Heads:	_		
Ty	/pe:	Hazard:	Density:	
I,	Oregon Construction Contractors Board Nothe following is true and reasonably defines the scope of work for this project:			
certify the following is	true and reasonably de	efines the scope of wo	rk for this project:	
b) Positions of sprink complies with curr (c) The proposed world (d) Only one sprinkler installed when each (e) The area covered proposed for Tenant improvement (e) Section 8.3.3.1 for (f) The installation shall (h) Piping shall not be (ii) Final approval shall (iii)	ent adopted edition of lack does not require hydrachead will be installed to head is in a separate for sprinkler head is limited in a new building state exceptions).  all comply with the requestion concealed until hanger labers be subject to onsite to	chitectural features such NFPA 13. aulic calculations. from one drop (except fire area). nited to the spacing rechall be equipped with quirements of the currers and bracing are inspects and inspections.	ch as soffits, beams, partitions, walls, etc.  ion: up to two heads from one drop may be quirements of NFPA 13.  Quick Response heads (see 2002 NFPA 13, ent adopted edition of NPFA 13.	
	nd the following is requ			
Building fire p	protection system peri	mit.	vithin the building's structure.  ned shall be available for all inspections.	
Print Name:				